

PermEscape™ Inc.

PROPER SET UP AND USE

1. The load rating when installed properly is 600 lbs and the recommended window opening is 32 inches high and 20 inches wide with a maximum sill depth of 12 inches.
2. Close doors before opening any windows to prevent fire from being drawn into the room.
3. Keep body close to ladder.
4. Unless absolutely necessary do not carry a child when using this ladder.
5. Do not carry pets or miscellaneous objects when using this ladder.
6. Instruct family members to use the escape ladder only when the primary escape path (that is, the main exit) is blocked or unsafe to use.
7. This escape ladder is not a toy or recreational device. Instruct children that the ladder is to be used only in an emergency.
8. For use only in windows that are structurally safe for the intended load.
9. Not recommended for use with storm windows or other windows that do not open to the recommended minimum dimensions (32 inches high and 20 inches wide).
10. Make sure ladder is correct length.
Do not use above 2 or 3 story height.

PE1200 - 12 ft.

PE1500 - 15 ft.

PE1800 - 18 ft.

PE2100 - 21 ft.

11. After assembly, plan and practice drills to ensure that occupants are familiar enough for proper use. This ladder is intended to supplement (not replace) the more important fire protection principles of fire drills, fire extinguishers, etc.
12. The ladder should be periodically inspected for damage, loosening of any assembled items, incorrect assembly, or significant deterioration of the materials of construction.
13. The ladder is designed for one person at a time.

SPECIAL INSTRUCTIONS

1. Any internal obstructions that could deter proper use of the ladder must be kept clear of the fire escape or kept at a safe distance.
2. Always check for external obstructions before extending the ladder. Keep exterior clear of any items that may cause improper functioning of the ladder.
3. Do not attempt to use the ladder if the window sill is wider than 12 inches.